

MATERIAL SAFETY DATA SHEET

Section I: Material Identification

Berry Plastics
201 Circle Drive No. #116
Piscataway, NJ 08846
732-356-2870

Emergency Phone:
Chemtrec 1-800-424-9300

Product Code: 5010 IA
Updated: 11/10/11

Section II: Toxic and Hazardous Ingredients

Hazardous Components	C.A.S. #	ACGIH TLV		OSHA		%
		TWA	STEL	TWA	STEL	
Toluene	108-88-3	50ppm		100ppm	150ppm	47
Acetone	67-64-1	750ppm	1000ppm	1000ppm		10
Methyl Ethyl Ketone	78-93-3	200ppm	300ppm	200ppm		10
Dibutyl Phthalate	84-74-2	400ppm				6

Section III: Physical/Chemical Characteristics

Form: Liquid Odor: Solvent Appearance/Color: Yellow
Sp. Gr: N/A Boiling Point: N/A Solubility in Water at 29°C: Insoluble
% Volatile by Weight: N/A Evaporation Rate (N-Bu.Ac.=1): N/A
Vapor Pressure (mm of Hg at 20°C): N/A Vapor Density: N/A
pH: N/A Stability: Stable

Section IV: Fire and Explosion Hazard

For fires involving this material, do not enter without proper protection equipment, including self-contained breathing apparatus.

Usual Fire and Explosion Hazards: None

Flash Point (Method Used): TCC 48°F (for toluene), 25°F (for M.E.K.)

Flammable Limits %: LEL – 1.2, UEL – 7.1 (for toluene)
LEL – 1.8, UEL – 11.5 (for M.E.K.)

Extinguishing Agents: Dry chemical, water spray, fog, CO₂, foam, sand/earth

Section V: Health Hazards

Permissible Concentrations: N/A Effects of Overexposure: None Determined

Toxicological Properties: skin and eye irritant

Emergency First Air Procedures:

Eyes: Flush immediately with water for 15 minutes. Consult a physician.

Skin: Wash with plenty of water for 15 minutes.

Inhalation: N/A

Ingestion: Consult a physician. Do Not Induce Vomiting.

Section VI: Control and Protective Measures

Ventilation Required: Mechanical exhaust to remove vapors.

Respiratory Protection: Use NIOSH approved respirator if TLV limits are exceeded.

Skin Protection: Gloves, rubber or plastic, solvent resistant

Eye Protection: Safety goggles or full-face mask

Hygienic Work Practices: Keep area clean, clean up spills immediately, Practice good personal hygiene.

Section VII: Precautions for Safe Handling and Use/Leak Procedures

Procedures for Cleanup: Absorb with sand, earth, vermiculite. Sweep up and dispose of in accordance with federal, state and local regulations.

Waste Disposal: Dispose of in accordance with federal, state and local regulations.

Handling and Storage: Store in a cool, dry area, away from flame, sparks, excessive heat.

D.O.T. Shipping Name: Adhesive,3,UN1133,PGII HMIS Rating: Health : 2

D.O.T. Label: Flammable Liquid

Flammability: 3

Reactivity: 0

Section 313 (Title III Superfund Amendment and Reauthorization Act): Toluene, M.E.K., D.B.P.

Carcinogen: No

The statements, technical information, and recommendations contained herein are believed to be reliable, however, they are given without warranty or guarantee of any kind, express or implied, and Berry Plastics assumes no responsibility for any loss, damage, direct or consequential, arising from the use of this product.

